

II. IN THE CLAIMS

1. (currently amended) A system for synchronizing the operation of a transmitter clock and a local reference clock, said system comprising:

a transmitter block, said transmitter block for transmitting consecutive synchronization
5 messages, each of said messages having a timestamp, said transmitter block maintaining a transmitter counter having a value, wherein each of said timestamps indicates said value of said counter at successive moments of time;

a receiver, coupled to said transmitter block, for receiving said synchronization messages;

first and second synchronization registers, coupled to said receiver, said synchronization
10 registers storing said timestamps of said consecutive synchronization messages;

a first comparator for comparing ~~the~~ values of said first and second synchronization registers to produce a synchronization time period;

first and second local reference registers, coupled to said local counter, each of said registers having a value indicative of a local reference counter at successive moments of time;

15 a second comparator, coupled to said first and second local reference registers, said comparator comparing the values of said first and second local registers and determining a local reference time period; and

a comparison and clock adjustment block, coupled to said first and second comparators and said local clock, said block comparing said synchronization time period with said local
20 reference time period and then adjusting said local reference clock based upon said comparison.

2. (currently amended) The system of claim 1 wherein data is transmitted from said transmitter to said receiver, said system further comprising:

a processor block, coupled to said receiver, for determining ~~the~~a transmission rate of said data; and

a comparison and clock adjustment block, coupled to said local reference counter and said processor block, for adjusting said local reference counter based upon said determination of
5 said rate.

3. (currently amended) The system of claim 2 wherein said comparison and clock adjustment block comprises a plurality of clock adjusters and CODEC clock generators, coupled to said processor block, for adjusting ~~a~~ digital-to-analog converter clock based upon said
10 determination of said rate.

4. (currently amended) The system of claim 1 wherein said transmitter further comprises a controller, said controller generating a strobe, said strobe delayed from the transmission of ~~said~~ data by a programmable amount.

15 5. (original) The system of claim 1 wherein said transmitter also transmits a MAP message to said receiver, said MAP message instructing said receiver to create a message having a TDMA format.

20 6. (original) The system of claim 1 wherein said comparison and clock adjustment block includes a voltage controlled oscillator.

7. (original) The system of claim 1 wherein said comparison and clock adjustment block includes a pulse stretcher.

8. (cancelled without prejudice) A method for synchronizing two clocks of a first
5 and second device comprising the steps of:

sending successive synchronization messages from said first device to said second device,
said synchronization message having a timestamp;

receiving said successive synchronization messages at said second device and
determining a synchronization period between said successive timestamps;

10 determining the period of said second clock of said second device;

comparing said synchronization period with said period of said second clock of said
second device, wherein said comparison determines a difference; and

adjusting the period of said second clock based upon said difference.

15 9. (cancelled without prejudice) The method of claim 8 comprising the further steps
including:

sending data from the first device to the second device;

receiving said data at said second device;

determining the rate of the data; and

20 adjusting the rate of said second clock based upon said rate of said data.

10. (cancelled without prejudice) The method of claim 9 wherein the rate of said
second clock is adjusted using a voltage controlled oscillator.

11. (cancelled without prejudice) The method of claim 9 wherein the rate of said second clock is adjusted using a pulse stretcher.

5 12. (cancelled without prejudice) The method of claim 9 comprising the further steps of:

sending a MAP message from said first device to said second device, said MAP message instructing said second device to said first device in a TDMA format.

10 13. (cancelled without prejudice) A cable modem, said cable modem adjusting the rate of a clock, said cable modem comprising:

a clock having a period;

means for receiving successive synchronization messages, each of said synchronization message containing a timestamp;

15 means for determining the period of said local clock;

a comparator for comparing the rate of said local clock with the period between successive timestamps in successive synchronization messages;

means for adjusting the period of said local clock based upon said comparison.

20 14. (cancelled without prejudice) The cable modem of claim 13 further comprising:

means for receiving data;

means for determining the rate of said data; and

means for adjusting the rate of said local clock based upon said comparison.

15. (cancelled without prejudice) The cable modem of claim 13 wherein said comparator uses a voltage controlled oscillator.

5 16. (cancelled without prejudice) The cable modem of claim 13 wherein said comparator uses a modulo comparator.

17. (currently amended) A system comprising:
a hybrid fiber coax network;
10 a cable telephone modem (CTM) coupled to said hybrid fiber coax network, said modem having a local clock;

a cable modem termination system (CMTS) coupled to said hybrid fiber coax network and a packet network, wherein said CMTS includes means for sending successive synchronization messages, each of said synchronization messages having a timestamp, to said
15 cable telephone modem;

wherein said cable telephone modem includes means for receiving said synchronization messages and determining a synchronization period, wherein said synchronization period is ~~the~~a time between successive timestamps; means for determining ~~the~~a period of said local clock; means for comparing said period of said local clock with said synchronization period to
20 determine a difference, and means for adjusting said period of said local clock based upon said difference.

18. (currently amended) The system of claim 17 wherein said CTM includes means for receiving data from said CMTS, means for determining ~~the~~a rate of said data, and means for adjusting the period of said local clock based upon said rate.